



CEILING PAINT

Economical Ceiling Paint

TECHNICAL DATA SHEET

Product Type: Water-based acrylic ceiling paint
Appearance: Smooth, viscous white liquid
Application: Ready-to-use interior ceiling coating

Product Description:

ImvulaSeal Ceiling Paint is a cost-effective, water-based acrylic coating formulated for interior ceiling applications. It provides a smooth matt finish with good hiding power, helping to cover minor surface imperfections while delivering a uniform appearance.

Designed for ease of use, this paint offers low splatter during application and dries quickly, making it suitable for both professional contractors and DIY users. It is ideal for projects where affordability and functionality are key considerations.

Key Features & Benefits

- Cost-effective solution for ceiling applications
- Good opacity and coverage
- Smooth matt finish to reduce light reflection
- Easy application with minimal splatter
- Quick drying for faster project completion
- Low odour and user-friendly
- Suitable for a variety of interior ceiling surfaces

Typical Properties:

Property	Value
Appearance	White viscous liquid
Density (@ 25°C)	~1.45 – 1.60 g/cm ³
Ph	~8 - 9
Viscosity	Medium to High
Flash Point	Not applicable (water-based)
Shelf Life	12 months (unopened, cool storage)

Recommended Uses:

InvulaSeal Ceiling Paint is suitable for:

- Interior ceilings (plaster, gypsum board, concrete)
- Residential and commercial buildings
- New and previously painted surfaces
- Areas where a non-washable, matt ceiling finish is required

Surface Preparation:

For best performance:

- Ensure surfaces are clean, dry, and free from dust and contaminants
- Remove loose or flaking paint
- Repair cracks and imperfections with suitable filler
- Prime porous or chalky surfaces with a bonding liquid or primer

Application Instructions

For best performance:

- Stir well before use
- Apply using brush, roller, or airless spray
- Apply 2 coats for optimal coverage and finish
- Allow sufficient drying time between coats

Clean tools and equipment with water immediately after use

Drying Times

(At 25°C and 65% relative humidity)

- Touch Dry: 30 minutes – 1 hour
- Recoat Time: 2 – 4 hours
- Full Cure: 24 hours

Note: Drying times may vary depending on temperature and humidity.

Coverage

- Coverage will depend on surface porosity and texture
- Typical: $\pm 3 - 5$ m² per litre per coat (estimate)

Precautions:

- For interior use only
- Not suitable for high moisture or high traffic areas
- Do not apply to damp or wet surfaces
- Avoid application in extreme temperatures (<5°C or >35°C)
- Ensure adequate ventilation during application
- Keep out of reach of children

Packaging & Storage:

Packaging Sizes	Commonly 5L, and 20L containers
Storage Conditions	Store in cool, dry place above 5°C Keep container tightly sealed when not in use
Shelf Life	12 months (unopened)

Manufactured by:

ACOX TRADING (Pty) Ltd
Unit 15, 31 Rorich Avenue, Pumelani AH, Pretoria, South Africa
Reg. No.: 2023/227340/07 | VAT No.: 484 031 6097
E-mail: sales@acoxtrading.com