



SUPER SEAL

Economic Rubber paint

TECHNICAL DATA SHEET

Product Type: Economical Water-based Rubber Paint
Appearance: Viscous liquid in various colours
Application: Ready-to-use hydrophobic treatment

Product Description:

ImvulaSeal Super Seal is a high-performance, water-based rubber paint designed to provide a durable, seamless waterproofing coating for a variety of substrates. The product cures to form a flexible, continuous membrane that offers excellent adhesion and long-lasting protection against water ingress.

Its easy application and cost-effective formulation make it ideal for both residential and commercial maintenance applications, suitable for interior and exterior use.

Key Features & Benefits

- Forms a seamless, waterproof membrane
- Excellent adhesion to properly prepared surfaces
- Flexible rubberised coating to accommodate surface movement
- Easy to apply by brush or roller
- Suitable for interior and exterior applications
- Cost-effective waterproofing solution
- Good resistance to weathering conditions

Typical Properties:

Property	Value
Appearance	Viscous liquid in various colours
Density (@ 25°C)	~1.20 – 1.28 g/cm ³
Ph	~7 - 9
Viscosity	125 – 135 KU
Flash Point	Not applicable (water-based)
Shelf Life	12 months (unopened, cool storage)

Recommended Uses:

ImvulaSeal Super Seal is suitable for application on:

- Flat concrete roofs
- Flashings
- Galvanised and metal roof sheeting
- Concrete slabs and walls
- Gutters
- General maintenance waterproofing areas
- Membrane needs to be used on roof sheet joins and surface cracks

Surface Preparation:

Proper surface preparation is critical for optimal performance:

- Ensure surfaces are clean, dry, and sound
- Remove all dust, oil, grease, algae, and contaminants
- Eliminate all loose or flaking paint
- Repair all cracks, holes, or damaged areas
- New concrete must be:
 - Fully cured
 - Free of laitance

Application Instructions

- Stir product thoroughly before use
- Do not dilute
- Apply directly onto the prepared surface
- Use a brush or roller for application
- Apply an even, uniform coat
- Allow first coat to dry before recoating
- Apply a minimum of two coats
- Additional coats recommended in high-risk or heavy exposure areas

*Immediately clean brushes or other tools used with clean water

Drying & Curing Times

(At 25°C and 65% relative humidity)

- Touch Dry: 2–4 hours
- Recoat Time: 8–12 hours
- Full Cure: 48 hours

Note: Drying times may vary depending on environmental conditions such as temperature and humidity.

Coverage

- Coverage will depend on surface porosity and texture
- Typical: $\pm 2-4$ m² per litre per coat (estimate)

Precautions:

- Do not apply to wet or damp surfaces.
- Avoid application at surface temperatures below 5°C or above 35°C.
- Do not apply during rain or high humidity conditions
- Not designed for permanent immersion
- Wear gloves and eye protection during application.
- Product is alkaline—avoid contact with skin and eyes.

Packaging & Storage:

Packaging Sizes	Commonly 5L, and 25L paint drums / containers
Storage Conditions	Store in cool, dry place above 5°C Keep container tightly sealed when not in use
Shelf Life	12 months (unopened)

Manufactured by:

ACOX TRADING (Pty) Ltd
Unit 15, 31 Rorich Avenue, Pumelani AH, Pretoria, South Africa
Reg. No.: 2023/227340/07 | VAT No.: 484 031 6097
E-mail: sales@acoxtrading.com