



VetraFlex

Water-based Textured Paint

TECHNICAL DATA SHEET

Product Type:	Water-Based Acrylic Textured Paint
Appearance:	Thick, granular paste available in various colours
Application:	Ready-to-use decorative and protective textured coating

Product Description:

ImvulaSeal Textured Paint is a durable, water-based acrylic coating designed to provide a decorative textured finish while offering added surface protection. The product creates a tough, weather-resistant layer that helps to hide surface imperfections and enhance the appearance of walls.

Its heavy-bodied formulation makes it ideal for both new and previously painted surfaces, delivering a consistent texture and long-lasting performance in exterior and interior applications.

Key Features & Benefits

- Provides an attractive textured finish
- Excellent hiding of surface imperfections and cracks
- Durable and weather-resistant coating
- Good adhesion to properly prepared substrates
- Suitable for interior and exterior use
- Easy application with brush, roller, or texture roller
- Low maintenance, long-lasting finish

Typical Properties:

Property	Value
Appearance	Thick granular paint
Density (@ 25°C)	~1.60 – 1.75 g/cm ³
Ph	~8 - 9
Viscosity	High
Flash Point	Not applicable (water-based)
Shelf Life	12 months (unopened, cool storage)

Recommended Uses:

InvulaSeal Textured Paint is suitable for application on:

- Exterior and interior plastered walls
- Concrete surfaces
- Brickwork (prepared and primed)
- Previously painted surfaces in sound condition
- Boundary walls and facades

Surface Preparation:

Proper surface preparation is essential:

- Ensure surfaces are clean, dry, and structurally sound
- Remove all dust, dirt, grease, and contaminants
- Eliminate loose or flaking paint
- Repair cracks and damaged areas
- Prime highly porous or powdery surfaces before application

Application Instructions

- Stir thoroughly before use
- Do not dilute unless absolutely necessary
- Apply using a brush, roller, or textured roller
- Spread evenly to achieve desired texture pattern
- Work in manageable sections to maintain consistency
- Allow first coat to dry before applying additional coats if required
- Apply at least one full coat; a second coat may be applied for improved durability

Clean tools with water immediately after use.

Drying & Curing Times

(At 25°C and 65% relative humidity)

- Touch Dry: 2 – 4 hours
- Recoat Time: 8– 12 hours
- Full Cure: 24 hours

Note: Drying times may vary depending on environmental conditions such as temperature and humidity.

Coverage

- Coverage depends on application thickness and texture profile
- Typical: $\pm 1-2$ m² per litre per coat (estimate)

Precautions:

- Do not apply to wet or saturated surfaces
- Avoid application in extreme temperatures (<5°C or >35°C)
- Do not allow product to freeze
- Ensure adequate ventilation during use
- Wear gloves and eye protection
- Avoid contact with skin and eyes

Packaging & Storage:

Packaging Sizes	Commonly 5L, and 25L containers
Storage Conditions	Store in cool, dry place above 5°C Keep container tightly sealed when not in use
Shelf Life	12 months (unopened)

Manufactured by:

ACOX TRADING (Pty) Ltd
Unit 15, 31 Rorich Avenue, Pumelani AH, Pretoria, South Africa
Reg. No.: 2023/227340/07 | VAT No.: 484 031 6097
E-mail: sales@acoxtrading.com